

The **USB READER** is the newest addition to the floorprotectorgroup of products for the fidbox® electronic monitoring system. It works only in conjunction with the fidbox® version 5.

With the USB reader and the accompanying software it is possible to take readings of the newest V5 fidbox® elements and take them directly into the notebook or to use in combination with a Professional handheld reader. It is also possible to perform all required fidbox® settings using the USB reader.

Please consult the FloorProtector handbooks for an explanation of how to read the saved data from the fidbox®



### Specifications

Type	active
Frequency	2.45 GHz
Protocol	proprietary
Transmission output	1 mW
Power supply	5 V DC (+/- 10%)
Power input	Max. 25 mA @ 5 V
Interface	5V USB
Baud rate	57600 B/s, 8-N-1 (Virtual COM Port)
Operating temperature	-30°C to +60°C
Storage temperature	-40°C to +70°C
Weight	25 g (50g with packing material)
Protection class	IP 20
Article number	17101100 (Please quote when ordering)

### Software

Fidbox Desktop, Fidbox mobile (User, Admin)	Reading, Writing, Settings, Analysis
Driver	<a href="http://www.ftdichip.com/Drivers/VCP.htm">www.ftdichip.com/Drivers/VCP.htm</a> - Windows, Windows Mobile, Linux, MAC